

# NOCTURNE AB

## REPOSE COLLECTION

HIGH  
PERFORMANCE  
COLLECTIONS

CONSTRUCTION STRUCTURE STRUKTUR STRUCTUUR	Tufting 5/64" cut pile Tufté 5/64" cut pile Getuftet 5/64" cut pile Getuft 5/64" cut pile	CASTOR CHAIR SUITABILITY CHAISE À ROULETTES STUHLROLLENEIGNUNG ROLSTOELGESCHIKTHEID	EN 985 A: intensive use
PILE MATERIAL COMPOSITION DU VELOURS POLMATERIAAL POOLMATERIAAL	100% PA 6,	STAIR SUITABILITY ESCALIERS TREPPENEIGNUNG TRAPPENGESCHIKTHEID	EN 1963 A: intensive use
PRIMARY BACKING SUPPORT TRÄGERMATERIAAL TUFTDOEK	Non woven PES Non tissé Vlies Felt	PERMANENTLY ANTISTATIC ANTISTATIQUE PERMANENT PERMANENT ANTISTATISCH PERMANENT ANTISTATISCH	ISO 6356 < 2 kV
SECONDARY BACKING DOSSIER RÜCKEN TAPIJTRUG	Action back	IMPACT NOISE RATING ISOLATION PHONIQUE TRITTSCHALLVERBESSERUNG GELUIDSISOLATIE	ISO 140-8 27 dB ΔLw
PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT	± 1.160 gr/m <sup>2</sup>	SOUND ABSORPTION ABSORPTION PHONIQUE SCHALLABSORPTIONSGRAD GELUIDSABSORPTIE	ISO 354 0.20 αw
TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT	± 2.200 gr/m <sup>2</sup>	THERMAL RESISTANCE RÉSISTANCE THERMIQUE WÄRMEDURCHLASSWIDERSTAND WARMTEDOORLAATWEERSTAND	ISO 8302 0,091 m <sup>2</sup> K/W
PILE HEIGHT EPAISSEUR DU VELOURS POLHÖHE POOLHOOGTE	± 5,6 mm	FASTNESS TO LIGHT SOLIDITÉ A LA LUMIÈRE LICHTECHTHEID LICHTECHTHEID	ISO 105-B02 ≥ 7 (33-90-93-197) ≥ 5 (24-38-54-95-96)
TOTAL HEIGHT EPAISSEUR TOTALE GESAMTHÖHE TOTAAL HOOGTE	± 7,7 mm	COLOUR FASTNESS TO WATER SOLIDITÉ À L'EAU WASSERECHTHEIT WATERECHTHEID	EN ISO 105-E01 ≥ 4-5
TUFT DENSITY NOMBRE DE POINTS NOPPENZAHL AANTAL PUNTEN	± 297.000/m <sup>2</sup>	RUBBING FASTNESS SOLIDITÉ AU FROTTEMENT REIBECHTHEIT WRIJFECHTHEID	EN ISO 105-X12 ≥ 4
PILE DENSITY DENSITÉ DU VELOURS POLROHDICHTHEIT POOLDICHTHEID	± 0,172 g/cm <sup>3</sup>	FIRE RESISTANCE COMPORTEMENT AU FEU BRENNVERHALTEN BRANDGEDRAG	EN 13501-1 Cfl-s1 (if glued)
CLASSIFICATION CLASSEMENT KLASSIFIKATION CLASSIFICATIE	EN 1307 32 - LC4	WIDTH LARGEUR BREITE BREEDTE	EN ISO 3018 ± 400 cm
DESIGN REPEAT CM RACCORD CM RAPPORT CM DESSINRAPPORT CM	-		
PRODIS / GUT	7EE03BBB		



ITC CO BV  
Kanegemstraat 15, B-8700 Tielit  
itc-carpets.com



EN 14041 <b>CE</b>
25
ITC CO BV Kanegemstraat 15 - BE 8700 Tielit
DOP: 1011#IEOACV
Textile Floor Covering EN1307 Notified Body 2401
my.itc-carpets.com